

§ 108.560

(b) The launching appliance must be designed and arranged so that in its ready to launch position, the distance from the lowest point on the lifeboat it serves to the water surface with the unit in its lightest seagoing condition does not exceed the lifeboat's certificated free-fall height.

(c) The launching appliance must be arranged so as to preclude accidental release of the lifeboat in its unattended stowed position. If the means provided to secure the lifeboat cannot be released from inside the lifeboat, the means to secure the lifeboat must be arranged as to preclude boarding the lifeboat without first releasing it.

(d) Each free-fall launching arrangement must be provided with a secondary means to launch the lifeboat by falls. Such means must comply with the requirements of §§108.550, 108.553, and 108.555. Notwithstanding §108.550(e), the launching appliance must be capable of launching the lifeboat against unfavorable conditions of list of 5 degrees in any direction and it need not comply with the speed requirements of §§108.553 (g), (h), and (i).

If the secondary launching appliance is not dependent on gravity, stored mechanical power or other manual means, the launching arrangement must be connected both to the unit's main and emergency power supplies.

§ 108.560 Rescue boats.

Each unit must carry at least one rescue boat. Each rescue boat must be approved under approval series 160.156. A lifeboat is accepted as a rescue boat if it also meets the requirements for a rescue boat.

§ 108.565 Stowage of rescue boats.

(a) Rescue boats must be stowed as follows:

(1) Each rescue boat must be ready for launching in not more than 5 minutes.

(2) Each rescue boat must be in a position suitable for launching and recovery.

(3) Each rescue boat must be stowed in a way that neither the rescue boat nor its stowage arrangements will interfere with the operation of any survival craft at any other launching station.

46 CFR Ch. I (10-1-13 Edition)

(4) Each rescue boat that is also a lifeboat, must be in compliance with §108.530.

(b) Each rescue boat must be provided a means for recharging the rescue boat batteries from the unit's power supply at a supply voltage not exceeding 50 volts.

(c) Each inflated rescue boat must be kept fully inflated at all times.

[CGD 84-069, 61 FR 25291, May 20, 1996, as amended at 63 FR 52814, Oct. 1, 1998]

§ 108.570 Rescue boat embarkation, launching and recovery arrangements.

(a) Each rescue boat must be capable of being launched with the unit making headway of 5 knots in calm water, or with the unit anchored or bearing on the bottom in a current of up to 5 knots. A painter may be used to meet this requirement.

(b) Each rescue boat embarkation and launching arrangement must permit the rescue boat to be boarded and launched in the shortest possible time.

(c) If the rescue boat is one of the unit's survival craft, the rescue boat must also be as follows:

(1) The rescue boat must meet the embarkation arrangement and launching station requirements of §108.540.

(2) The rescue boat must meet the launching arrangement requirements of §§108.550 and 108.557, and if the launching arrangement uses falls and a winch, §108.553.

(3) If the launching arrangement uses a single fall, the rescue boat must have an automatic disengaging apparatus approved under approval series 160.170, instead of a lifeboat release mechanism.

(d) Rapid recovery of the rescue boat must be possible when loaded with its full complement of persons and equipment. If the rescue boat is also a lifeboat, rapid recovery must be possible when loaded with its lifeboat equipment and an approved rescue boat complement of at least six persons.

(e) Each rescue boat launching appliance must be fitted with a powered winch motor.

(f) Each rescue boat launching appliance must be capable of hoisting the rescue boat when loaded with its full rescue boat complement of persons and

Coast Guard, DHS

§ 108.575

equipment at a rate of not less than 0.3 meters per second (59 feet per minute).

[CGD 84-069, 61 FR 25291, May 20, 1996, as amended at 63 FR 52814, Oct. 1, 1998]

§ 108.575 Survival craft and rescue boat equipment.

(a) All lifeboat and rescue boat equipment must be as follows:

(1) The equipment must be secured within the boat by lashings, storage in lockers, or compartments, storage in brackets or similar mounting arrangements or other suitable means.

(2) The equipment must be secured in such a manner as not to interfere with any abandonment procedures or reduce seating capacity.

(3) The equipment must be as small and of as little mass as possible.

(4) The equipment must be packed in a suitable and compact form.

(5) The equipment should be stowed so the items do not—

(i) Reduce the seating capacity;

(ii) Adversely affect the seaworthiness of the survival craft or rescue boat; or

(iii) Overload the launching appliance.

(b) Each lifeboat, rigid liferaft, and rescue boat, unless otherwise stated in this paragraph, must carry the equipment specified for it in table §108.575(b) of this section. A lifeboat that is also a rescue boat must carry the equipment in the table column marked for a lifeboat. Each item in the table has the same description as in §199.175 of this chapter.

TABLE 108.575(b)—SURVIVAL CRAFT EQUIPMENT

Item No.	Item	International service			Other than international service		
		Lifeboat	Rigid liferaft	Rescue boat	Lifeboat	Rigid liferaft	Rescue boat
1	Bailer ¹	1	1	1	1	1	1
2	Bilge pump ²	1			1		
3	Boathook	2		1	2		1
4	Bucket ³	2		1	2		1
5	Can opener	3	3				
6	Compass	1		1	1		1
7	Dipper	1			1		
8	Drinking cup	1	1				
9	Fire extinguisher	1		1	1		1
10	First-aid kit	1	1	1	1	1	1
11	Fishing kit	1	1				
12	Flashlight	1	1	1	1	1	1
13	Hatchet	2			2		
14	Heaving line	2	1	2	2	1	2
15	Instruction card		1			1	
16	Jackknife	1			1		
17	Knife ^{1 4}		1	1		1	1
18	Ladder	1		1	1		1
19	Mirror, signaling	1	1		1	1	
20	Oars (units) ^{5 6}	1		1			
	Paddles		2			2	
21	Painter	2	1	1	2	1	1
22	Provisions (units per person)	1	1				
23	Pump ⁷			1			
24	Radar reflector		1	1			
25	Rainwater collection device	1					
26	Repair kit ⁷			1			1
27	Sea anchor	1	2	1	1	2	1
28	Searchlight	1		1	1		1
29	Seasickness kit (kits/person)	1	1		1	1	
30	Signal, smoke	2	2		2	1	
31	Signal, hand flare	6	6		6	6	
32	Signal, parachute flare	4	4		4	4	
33	Skates and fenders ⁸	1			1		
34	Sponge ⁷		2	2		2	2
35	Survival instructions	1	1		1	1	
36	Table of lifesaving signals	1	1		1	1	
37	Thermal protective aid (percent of persons) ⁹	10%	10%	10%	10%	10%	10%
38	Tool kit	1			1		
39	Towline ¹⁰	1		1	1		1
40	Water (liters per person)	3	1.5		3	1	
41	Whistle	1	1	1	1	1	1

Notes: